











11 SERIES

	Rear Weight	Rated Operating Capacity*			⚠ Tipping Load ⚠		
		1	2	3	1	2	3
							
	0 kg	1417 kg 3124 lbs	1188 kg 2619 lbs	653 kg 1441 lbs	1771 kg 3904 lbs	1485 kg 3274 lbs	817 kg 1801 lbs
	340 kg 750 lbs	2089 kg 4605 lbs	1564 kg 3448 lbs	860 kg 1896 lbs	2611 kg 5756 lbs	1955 kg 4310 lbs	1075 kg 2371 lbs
	600 kg 1323 lbs	2544 kg 5609 lbs	1808 kg 3986 lbs	994 kg 2192 lbs	3180 kg 7011 lbs	2260 kg 4982 lbs	1243 kg 2740 lbs
	0 kg	1133 kg 2499 lbs	950 kg 2095 lbs	523 kg 1152 lbs	1417 kg 3124 lbs	1188 kg 2619 lbs	653 kg 1441 lbs
	340 kg 750 lbs	1567 kg 3454 lbs	1173 kg 2586 lbs	645 kg 1422 lbs	1958 kg 4317 lbs	1466 kg 3233 lbs	806 kg 1778 lbs
	600 kg 1323 lbs	1781 kg 3926 lbs	1266 kg 2790 lbs	696 kg 1535 lbs	2226 kg 4907 lbs	1582 kg 3488 lbs	870 kg 1918 lbs

 REFER TO THE OPERATOR MANUAL FOR THE COMPREHENSIVE LOAD DIAGRAM. THE INDICATED VALUES INCLUDE THE WEIGHT OF THE ASSEMBLED PALLET FORK, SO THE NET VALUE IS THE VALUE SHOWN IN THE TABLE MINUS THE WEIGHT OF THE PALLET FORK.

* EN 474-3:2006 + A1:2009 - FORK APPLICATION

